


- Screened coaxial IEPE sensor cable
- FEP Jacket
- -50°C to +200°C range
- Ideal for IEPE accelerometer sensors
- Blue jacket colour
- Nominal diameter 1.9mm
- 10/32UNF Microdot to 10/32UNF Microdot
- Length 5m±5%




Kemo Ltd has been making high quality signal conditioning equipment since 1965 and during this time we have worked with many of the World's largest companies and witnessed many examples of poor quality instrumentation cables. To resolve this problem Kemo started to produce its own specialist cable assemblies for the sensor and instrumentation market.

The cables we produce are assembled by Kemo using the highest quality cable and connectors that meet our exacting standards.

Attention is paid to strain relief and correct crimping. Every cable is fully tested and the capacitance checked prior to despatch.

10/32UNF microdot connector	
Physical	Value
Body	Nickel Plated Brass
Knurl nut	Nickel Plated Brass
Centre Conductor	Gold plated brass
Insulator	PTFE
Strain relief boot	Rubber
Temperature Range	-70°C to +260°C

Cable Electrical Properties	Value
Impedance	50 ±2Ω
Max. Capacitance	100nF/km
Max. Conductor Resistance	355Ω/km
Min. Insulation Resistance	>5000 MΩ/km
Voltage rating	500VAC
Test voltage	3kV DC
Max. Attenuation	108dB/100m
Temp rating	-50°C to +200°C
Min Bending radius	Fixed: 10mm
Min Bending radius	Flexing: 20mm



Layer	Description	Material	Overall diameter
1	Central conductor – multi strand	Silver plated copper clad steel 30AWG (7/0.102mm)	0.30mm
2	Dielectric/Insulation	PTFE	0.86mm ±0.05mm
3	Screen/Outer conductor	Silver Plated Copper Braid 96% coverage	1.35mm
4	Outer jacket	FEP	1.9mm nom.

Due to continued product development Kemo Limited reserve the right to change specification without notice.