

- Screened 6 core cable
- PVC Jacket
- -20°C to +80°C range
- Black jacket colour
- Nominal diameter 3.6mm
- Lemo® 7 Pin 1B Male plug connector
- Lemo® 7 Pin 1B Female socket connector
- Lemo® Strain relief
- Length 30m±5%
- Other lengths available



The L7JL7S-300 is a 30m extension cable assembly developed for use with a range of microphones from manufacturers such as Bruel & Kjaer (HBK), Gras, PCB Piezotronics and others using the Lemo® 7 pin 1B connection.

Units include but are not limited to:

- B&K (HBK) 2670 ¼" Microphone Preampfier
- B&K (HBK) 2669-C ½" Microphone Preampfier
- B&K (HBK) 2669-L ½" Microphone Preampfier
- GRAS 26AM ½" Standard Preampfier
- GRAS 26AS ¼" Standard Preampfier
- GRAS 26HG ¼" Preampfier
- GRAS 26AI ½" Preampfier
- PCB 426A30 ½" Preampfier
- PCB 426B31 ¼" Preampfier

Featuring a lightweight 6 core screened cable of just 3.6mm diameter which keeps the mass of even long cables down to a manageable level.

Kemo uses only genuine Lemo® parts including the required strain relief connected to the Z nut version of the connectors.

Other cable lengths are available, please enquire for stock availability.



Lemo® is a registered trademark of Lemo S.A. Switzerland, only genuine Lemo products used.

Due to continued product development Kemo Limited reserve the right to change specification without notice.

Kemo Limited

First Floor, 33 King Street, Thetford, Norfolk, IP24 2AW, United Kingdom

+44 (0)1474 705168

www.kemo.com sales@kemo.com