


- Screened 6 core cable
- PVC Jacket
- -20°C to +80°C range
- Black jacket colour
- Nominal diameter 3.6mm
- Lemo® 7 Pin 1B Male plug connector
- Lemo® 7 Pin 1B Female socket connector
- Lemo® Strain relief
- Length 30m±5%
- Other lengths available



The L7JL7S-300 is a 30m extension cable assembly developed for use with a range of microphones from manufacturers such as Bruel & Kjaer (HBK), Gras, PCB Piezotronics and others using the Lemo® 7 pin 1B connection.

Units include but are not limited to:

- B&K (HBK) 2670 ¼" Microphone Preamplifier
- B&K (HBK) 2669-C ½" Microphone Preamplifier
- B&K (HBK) 2669-L ½" Microphone Preamplifier
- GRAS 26AM ½" Standard Preamplifier
- GRAS 26AS ¼" Standard Preamplifier
- GRAS 26HG ¼" Preamplifier
- GRAS 26AI ½" Preamplifier
- PCB 426A30 ½" Preamplifier
- PCB 426B31 ¼" Preamplifier

Featuring a lightweight 6 core screened cable of just 3.6mm diameter which keeps the mass of even long cables down to a manageable level.

Kemo uses only genuine Lemo® parts including the required strain relief connected to the Z nut version of the connectors.

Other cable lengths are available, please enquire for stock availability.



Lemo® is a registered trademark of Lemo S.A. Switzerland, only genuine Lemo products used.

Due to continued product development Kemo Limited reserve the right to change specification without notice.

#### Kemo Limited

First Floor, 33 King Street, Thetford, Norfolk, IP24 2AW, United Kingdom

+44 (0)1474 705168

[www.kemo.com](http://www.kemo.com) [sales@kemo.com](mailto:sales@kemo.com)